



A Professional Touch Products Manufacturer!



Model: KOT-0150U-CA4P

**15" LCD Open Frame PCAP touch monitor
(dust-proof type)**

Features & Application & Accessories

Features

- **Long-lasting product cycle-enclosure controlled by KeeTouch specifications, so that future upgrades do not bring external size changes.**
- **High brightness, high contrast ratio and broad viewing angle.**
- **Multiple mounting options including horizontal bracket mount, vertical bracket mount and VESA mount.**
- **USB touch interface port.**
- **VGA and DVI input video format.**
- **CCC, ETL, FCC, CE, CB, RoHS certificates.**

Application

- **Banking**
- **Hospitality**
- **Transport and Ticking**
- **Outdoor and indoor Kiosks**
- **Gaming/Casino Systems**
- **Entertainment**
- **Customized Solutions**

Accessories

- **Power Cable: A North American power cable or an European power cable or a Chinese standard power cable is included to the end user's area.**
- **Power Supply Brick: A power supply brick is included.**
- **Touch/Video Cables: USB touch cable, VGA and DVI cable are included.**

15" LCD Open Frame PCAP touch monitor (dust-proof type)



A Professional Touch Products Manufacturer!

K Specification

Model No.	KOT-0150U-CA4P	
Series	OT, dust-proof	
Display type	4:3 ratio 15 " a-Si TFT active matrix	
Display Active Area	304.1 (H) ×228.1 (V)	
Monitor Dimensions	Width: 348 mm Height: 272 mm Depth: 47.5 mm	
Resolution	1024 X 768@60Hz	
Colors	16.7 million	
Brightness	Pure LCD panel	250 cd/m ²
	With CA glass sensor panel	217 cd/m ²
Response time	8 ms	
Viewing angle (typ. at CR>10)	Horizontal (left/right): 160° (80°/80°)	
	Vertical (up/down): 160° (80°/80°)	
Contrast ratio	600:1	
Video input	VGA and DVI	
Frequency (H/V)	30~80 KHz / 60~75 Hz	
Power supply	Type: power brick Input (line) voltage: 100-240 VAC, 50-60 Hz	
Environment	Operation Temp:	0~50°C
	Storage Temp:	-20~60°C
	Operation RH:	20%~80%
	Storage RH:	10%~90%
MTBF	40,000 hours	
LED back light life	40,000 hours	
Weight (N.W/G.W)	3.5 kg (1pc) / 8 kg (2 pcs in one package)	
Package dimensions	429×183×356 (mm) (2 pcs in one package)	
Power consumption	Max.16 W	
Standby power consumption	0.80 W	
Mount interface	1)VESA 75 mm and 100 mm 2)Mount bracket, horizontal or vertical	
OSD control	Buttons	AUTO,+,POWER,-,MENU
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Touch screen type	15" Projected Capacitive 4 mm touch sensor, 10 points in Win 7, 1point in XP	
Touch system interface	USB	
Touch response time	≤ 10ms	
Agency approval	CCC, ETL, FCC, CE, CB, RoHS	
Regular warranty	3 years	

NOTE: The display SPEC. will change follow the relevant LCD panel brand and model



A Professional Touch Products Manufacturer!

Mechanical Dimensions

