



Model: KOT-0150U-RE2.2P

**15" LCD Open Frame resistive touch monitor
(dust-proof type)**

Specification

Model No.	KOT-0150U-RE2.2P	
Series	OT, dust	
Display Type	4:3 ratio 15 " a-Si TFT active matrix	
Display Active Area	304.1 mm (H) × 228.1 mm (V)	
Monitor Dimensions	Width: 348 mm Height: 272 mm Depth: 47.5 mm	
Resolution	1024 × 768 @ 60 Hz	
Colors	16.7 Million	
Brightness	Pure LCD panel	250 cd/m ²
	Resistive	200 cd/m ²
Response Time	8 ms	
Viewing Angle (typ. at CR>10)	Horizontal (left / right)	80°/80°
	Vertical (up / down)	80°/80°
Contrast Ratio	600:1	
Video Input	VGA and DVI	
Frequency (H / V)	30~80 KHz / 60~75 Hz	
Power Supply	Type: Power brick Input voltage: 100-240 VAC, 50-60 Hz	
Environment	Operating Temp:	0~50°C
	Storage Temp:	-20~60°C
	Operating RH:	20%~80%
	Storage RH:	10%~90%
MTBF	40,000 hours	
LED Back Light Life	40,000 hours	
Weight (N.W / G.W)	3.2 kg (1 pc) / 7.5 kg (2 pcs in one package)	
Package Dimensions	429 mm * 356 mm * 183 mm	
Mount Interface	1) VESA 75 mm and 100 mm 2) Mount bracket, horizontal or vertical	

OSD Control	Buttons	AUTO, +, POWER, -, MENU
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Touch Screen Type	15" resistive touch screen	
Touch System Interface	USB	
Touch Response time	≤10 ms	
Agency Approval	CCC, ETL, FCC, CE, CB, RoHS	
Regular Warranty	3 years	

NOTE: The display SPEC. will change follow the relevant LCD panel brand and model

Mechanical Dimensions:

