



**Symphone
N2S**
Android
smartphone
computer



FEATURES

Excellent scanning performance.

The N2S is armed with a high performance 1D/2D scanning module, ideal for day in and day out heavy scanning.

First time everytime barcode scanning.

The N2S has a 25 degree scan angle, making scanning easy and comfortable while reading the screen.

Built to withstand heavy use.

A durable design, reinforced by carefully selected materials, guarantees low maintenance costs even for use in harsh conditions.

High quality PCAP Touch.

The N2S supports both dry and moist hands, as well as gloved fingertip touch input. Ideal for use in severe conditions, such as rain, snow and dust.

Supplied with Symphone N2S charging cradle.



Symphone N2S with charging cradle.

Application Scenarios

Warehouse management • Inventory counting • manufacturing • access control • back office • inventory management • stock management • food traceability.

Symphone N2S

Android smartphone computer

newland-id.com

Physical Specifications	Model	N2S		
	Dimensions	169*72*23.8mm		
	Keys	Front: Number keys, Five-navigation key, Back key, Del key Enter/End key, Dial key, Self-definition (F1, F2, F3) keys Sides: Power key, Left-scan key, Right-scan key, Function key		
	Input	English, pinyin, handwriting, soft-keyboard		
Product Performance	OS	Android 5.1		
	CPU	Dual-core 1.2 GHz		
	Screen	IPS, 3.5 inch WVGA, 480*800 pixel		
	Touch	Multi-point PCAP (Projective Capacitive Touch)		
	Memory	ROM	4GB	
		RAM	1GB	
	Operating Temperature	-20°C~55°C		
Barcode Scanning	1D	Code39, Codabar, Code128, Interleaved 2 of 5, UPC, EAN, MSI and more		
	2D (optional)	QR, PDF417, DataMatrix, MaxiCode and more		
Network	Wi-Fi	IEEE 802.11 b/g/n		
	WCDMA/GSM	WCDMA: 2100 MHz / GSM: 900 MHz, 1800 MHz		
	Bluetooth	BT 3.0 + HS, BT v2.1 + EDR		
	Camera	High-definition, auto focus		
	GPS	GPS, AGPS		
Battery	Capacity	4000mAh		
Endurance	Standby	500 hours		
	Talking	20 hours		
Ports & Accessories	T-Flash	Micro SD/TF (up to 32 GB)		
	SIM	Mini-SIM card		
	Jack	Micro USB, 3.5mm Audio jack, DC jack		
	Charging stand (included)	Charges device and battery at the same time		
	Others	Printer (optional) supports BT-connected devices, Adapter, Cable, Belt		
Certificates & Protection	Industrial protection	IP64		
	Drop	1.5 meter drop to concrete		
	Certificates	CTA, CCC, CE, RoHS		
	Laser Safety	IEC2 / FDA II, IEC60825 / EN60825-1		

Specifications are subject to change without notice.

Version: V1.0

Newland EMEA HQ

+31 (0) 345 87 00 33
info@newland-id.com
newland-id.com

D-A-C-H

+49 (6) 182 82916-16
info@newland-id.de

United Kingdom

+44 (0) 1442 212020
sales@newland-id.co.uk

France

+39 (0) 345 8804096
france@newland-id.com

Russia

+31 (0) 345 87 00 33
russia@newland-id.com

Benelux

+31 (0) 345 87 00 33
benelux@newland-id.com

Turkey

+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica

+34 (0) 93 303 74 66
info@newland-id.es

Middle East

+39 (0) 345 8804096
middleeast@newland-id.com

Italy

+39 (0) 342 0562227
italy@newland-id.com

South Africa

Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic

+46 (0) 70 88 47 767
nordic@newland-id.com

Iran

+90 (0) 544 538 40 49
iran@newland-id.com