

#### Mobile Computers UHF Pistol Grip





side and front of the SD60RT

**SD60RT Hercules** Mobile Computer - UHF Pistol Grip

## Comfortable design, simplicity of use and a back-up battery make this mobile computer ultra reliable.

Retail • Ticketing

# Image: Second second

#### About the product

- Supports 1D and 2D barcodes
- Built on Android 8.1
- 6.0 inch (2160x1080) 5 point capacitive touch screen
- Octa-core 2.0GHz

- Support HF and UHF simultaneously
- Offers: WIFI 802.11 a/b/g/n (2.4GHz & 5GHz),
  - Bluetooth 4.1, GPS, Camera, NFC, UHF, GSM, WCDMA
- Supplied with cradle

#### Accessories



charging cradle (included)



### **Technical specifications**

MODEL	SD60RT
CPU	Octa-core 2.0GHz
OS	Android 8.1
RAM	4GB
ROM	64GB
Camera	Rear 13MP AF, high brightness LED flash, front 5MP camera
Screen	6.0" IPS HD touch screen
Resolution	2160x1080
Touch screen	5-point capacitive touch screen
Dimension	160mm x 80mm x 15.8mm (grip length 110mm)
Weight (with battery)	600g
Battery capacity	PDA: built-in 6000mAh lithium battery, un-removable
	Grip: built-in 4000mAh lithium battery, removable
Charging	PE fast charge , full charge time < 4h
Bluetooth	BT4.1 BLE
Wi-Fi	IEEE 802.11 a/b/g/n 2.4G 5G dual frequency
WLAN	FDD-LTE B1/B3/B5/B7
	TDD-LTE B38/B39/ B40/B41
	TDSCDMA B34/B39
	WCDMA B1/B2/B5/B8
	GSM B2/B3/B5/B8
	CDMA 1 x/CDMA2000 BC0/BC1
GPS	GPS+BD+GLONASS
Audio	Front dual stereo speakers, Volume 90db±3db (test distance 10cm)
Interface	2 Micro SIM card slots
	1 Micro SD card slot
	USB Type-C
Keypad	2 volume buttons, 2 function buttons (1 left, right), 1 power button, 1 grip button
Notifications	Sound, vibration, LED
Operating temperature	-20°C - +55°C
Storage temperature	-30°C - +70°C
Humidity	5%-95%
ID alara	IP65
IP class	
IP class Drop	1 meter drop to cement floor
	1 meter drop to cement floor ± 15kV air discharge , ±8kV contact discharge
Drop	•
Drop ESD	± 15kV air discharge , ±8kV contact discharge CCC, CE
Drop ESD Certificates	± 15kV air discharge , ±8kV contact discharge
Drop ESD Certificates NFC	± 15kV air discharge , ±8kV contact discharge CCC, CE ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm
Drop ESD Certificates NFC	± 15kV air discharge , ±8kV contact discharge CCC, CE ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm ISO18000-6C
Drop ESD Certificates NFC	<ul> <li>± 15kV air discharge , ±8kV contact discharge</li> <li>CCC, CE</li> <li>ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm</li> <li>ISO18000-6C</li> <li>Euro frequency (865MHz - 867MHz)</li> </ul>
Drop ESD Certificates NFC	<ul> <li>± 15kV air discharge , ±8kV contact discharge</li> <li>CCC, CE</li> <li>ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm</li> <li>ISO18000-6C</li> <li>Euro frequency (865MHz - 867MHz)</li> <li>Antenna: 4dBi quadrifilar antenna</li> </ul>
Drop ESD Certificates NFC	<ul> <li>± 15kV air discharge , ±8kV contact discharge</li> <li>CCC, CE</li> <li>ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm</li> <li>ISO18000-6C</li> <li>Euro frequency (865MHz - 867MHz)</li> <li>Antenna: 4dBi quadrifilar antenna</li> <li>Power: 5dBm~33dBm adjustable, 1dbm step</li> </ul>
Drop ESD Certificates NFC RFID (UHF)	<ul> <li>± 15kV air discharge , ±8kV contact discharge</li> <li>CCC, CE</li> <li>ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm</li> <li>ISO18000-6C</li> <li>Euro frequency (865MHz - 867MHz)</li> <li>Antenna: 4dBi quadrifilar antenna</li> <li>Power: 5dBm~33dBm adjustable, 1dbm step</li> <li>Working range: Indoor &gt;18m, Outdoor &gt;8m</li> <li>Inventory speed: &gt;200 tags/sec</li> </ul>
Drop ESD Certificates NFC	<ul> <li>± 15kV air discharge , ±8kV contact discharge</li> <li>CCC, CE</li> <li>ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm</li> <li>ISO18000-6C</li> <li>Euro frequency (865MHz - 867MHz)</li> <li>Antenna: 4dBi quadrifilar antenna</li> <li>Power: 5dBm~33dBm adjustable, 1dbm step</li> <li>Working range: Indoor &gt;18m, Outdoor &gt;8m</li> <li>Inventory speed: &gt;200 tags/sec</li> <li>AZTEC, CODABAR, CODE11, CODE128, EAN128, CODE39, CODE49, CODE93,</li> </ul>
Drop ESD Certificates NFC RFID (UHF)	<ul> <li>± 15kV air discharge , ±8kV contact discharge</li> <li>CCC, CE</li> <li>ISO14443NB , ISO15693 , NFC Reading distance: 0~5cm</li> <li>ISO18000-6C</li> <li>Euro frequency (865MHz - 867MHz)</li> <li>Antenna: 4dBi quadrifilar antenna</li> <li>Power: 5dBm~33dBm adjustable, 1dbm step</li> <li>Working range: Indoor &gt;18m, Outdoor &gt;8m</li> <li>Inventory speed: &gt;200 tags/sec</li> </ul>