

# PICCO II

## 2-inch Thermal Receipt Printer



### Product Features

- Three-dimensional fashion appearance
- Alternative dual-mode Bluetooth 4.0
- USB error reprint function



Alternative  
dual-mode Bluetooth 4.0



Paper saving mode



Error reprint function

## Specification

Model	PICCO II	
Print Parameter	Print Method	Direct thermal line printing
	Resolution	203 dpi
	Print Speed	Max. 100 mm/s
	Print Width	48 mm
	Command	ESC/POS
	Page Mode	No
	Outfeed Direction	Forward
Paper	Paper Type	Thermal receipt paper
	Paper Width	58 mm
	Paper Thickness	0.05~0.08 mm
	Roll paper Diameter	Max. 60 mm
Character and Barcode	Character Specification	Simplified Chinese/traditional Chinese/Korean/Japanese, 47 codepage
Detection	Sensor	Paper end sensor, cover opening sensor, over-temperature sensor, over-voltage sensor
Barcode Printing	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Memory	RAM	256 KB
	Flash	4 MB
Cut Method		Tear bar
Reliability	TPH Life	100 KM
Interface	Default	USB-B, RS232, cash drawer 24V
	Optional	Dual-mode Bluetooth
Electrical Parameter	Input	AC100~240V, 50~60Hz
	Output	DC 12V, 2A
Environmental Parameter	Operating	0~40°C, 20~85%RH, non-condensing
	Storage	-20~60°C, 5~95%RH, non-condensing
Physical Parameter	Dimension(L*W*H)	110*105*114(mm)

## Application

