

*Easy
your work*

Entry level printer, Easy and simple to operate



FEATURES



- Ultra Modern 3D indicator light design
- Printer status with a quick look
- Large memory, large storage space
- The most affordable price
- Professional edition software

Resolution	203/300 dpi	
Print mode	Direct Thermal/Thermal Transfer	
CPU	32-bit CPU	
Memory	●RAM: 64MB SDRAM	●ROM: 128MB Flash ROM
Print speed	203 dpi 1 to 5 ips (option up to 6 ips) /300 dpi 4 ips	
Max. print length	150" (3810mm)	
Print width	4.1" (104mm)	
Sensor type	●Moveable reflective and gap sensor ●Ribbon sensor	●Cover open sensor
Display	N/A	
Control panel	●1 multi-functional keys	●6 status LED light
Media	●Maximum label width: 4.33" (110mm) ●Minimum label width: 0.59" (15mm) ●Maximum roll diameter: 5" (127mm) ●Core diameter: 1.0" (25.4mm)	●Media thickness: 0.002" (0.06mm) to 0.0075" (0.2mm) ●Media type: Continuous, die-cut, tag, fan-fold, black mark
Ribbon	●OD: 1.535" (39mm) ●Max length: 100m ●Width: 1.0" (25.4mm) to 4.3" (110mm)	●ID: 0.5" (12.7mm) ●Ribbon type: Wax, wax/resin, resin
Interfaces	●USB slave port	●Option: Ethernet port 10/100Mbps
1D barcodes	Code39 standard or extended, Code39 with check digit, Code93, Code128 UCC, Code128 auto A modes, Codabar, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 of 5 check digit, Interleaved 2 of 5 with human readable check digit, UCC/EAN 128, UPC A, UPC A 2&5 add-on, UPC E, UPC E 2&5 digit add-on, UPC Interleaved 2 of 5, Code11	
2D barcodes	Data Matrix, MaxiCode, PDF417, QR code	
Fonts	●5 internal expandable bitmap fonts (alpha-numeric) ●2 internal expandable bitmap fonts (numeric only)	●Downloadable soft font ●4 directions: 0, 90, 180, 270 degrees
Image	●PEPL: PCX, Direct binary graphic	●PDPL: PCX, BMP, HEX
Options	●Peeler kit ●Cutter	●Ethernet module, BT module, WiFi module
Power	●Switching power adapter ●Input: 100 to 240V, 1.8A, 50~60Hz	●Output: 24V, 2.5A
Audio	N/A	
Real Time Clock	N/A	
Environment	●Operation: 5°C to 45°C (40°F to 112.9°F)	●Storage: -20°C to 50°C (-4°F to 121.9°F)
Humidity	●Operation: 10% to 90% non condensing	●Storage: 5% to 95% non condensing
Printer dimension	●Width: 200.00mm (7.83") ●Length: 263.19mm (10.36")	●Height: 188.29mm (7.41") ●Weight: 2KG
Certification	CE, FCC class A, CB, CCC, BSMI	