

## NP-P2061M / NP-P2062M

- Fully upward compatible with NP-2021/2025 series
- Same external dimension as NP-2021 even with auto cutter (P2062M)



NP-P2061M-AW



NP-P2062M-BW



**NP-P20AR**

## NP-P2081D

- Super low price
- Super compact panel printer
- Color can be selected from two colors (-W:White, -B:Black).



NP-P2081D-W



NP-P2081D-B

Model name	NP-P2061M-AW NP-P2062M-AW	NP-P2061M-BW NP-P2062M-BW	NP-P20AR	NP-P2081D-W / NP-P2081D-B
Print method	Direct line thermal dot			
Print speed	Max. 100 mm / sec (DC8.5V)		Max. 75 mm / sec	
Resolution	8dots / mm (203dpi)			
Number of dots / line	384 dots			
Paper width	58mm			
Print width	48mm			
Paper diameter	Max. $\phi$ 50 mm			Max. $\phi$ 40mm
Character	English, Polish, Russian, Scandinavian, Turkish			
Barcode	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE128, CODE93, GS1 DataBar, QR Code (model2)		UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE128, CODE93	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODABAR, CODE128, QR Code (model2)
Interface	Parallel(Centronics),Serial(RS232C), and USB(V2.0 Full Speed)		Serial (RS232C)	USB (V2.0 full speed) and Serial (RS232C)
Cutter	NP-P2061M-AW/-BW : Tear bar NP-P2062M-AW/-BW : Auto Cutter		-	Tear bar
Operating voltage	DC5V ~ 8.5V		DC5 ~ 8.5V, DC3.3V (circuit voltage)	DC5V ~ 9V
External dimensions	101(W) x 66(D) x 116(H)mm	96(W) x 66(D) x 111(H)mm	77.7(W) x 105.1(D) x 49.5(H)mm (Horizontal setting only)	79.5(W) x 67.4(D) x 77.0(H)mm