



FUZZYSCAN SE380 Series OEM Scan Engine



A miniature scan engine that brings top performance and value to OEM applications

The SE380's outstanding capabilities and ultra-compact design are ideal for a wide range of OEM applications. Empowered by the FuzzyScan imaging platform, it easily captures a variety of 1D and stacked barcodes, whether displayed on paper, plastic or digital screens. This scan engine also provides superior motion tolerance, as well as a reading speed of up to 500 scans per second. The SE380 delivers the best value in its class, offering ease of integration along with exceptional scanning performance.

- Ultra-small and lightweight
- Easy to integrate
- Supports GS1 DataBar, PDF, MicroPDF and composite codes
- Superior readings on 3 mil barcodes, with a depth of field of over 3"
- Up to 34" reading range on regular barcodes
- Exceptional readings on low contrast, smudged, and damaged barcodes
- Superior motion tolerance for rapid captures of moving barcodes
- High speed scanning, up to 500 scans per second
- Supports various host interfaces: RS232, USB HID and USB COM
- Low power consumption

Scan All Your Needs

Capture Various Symbologies

This OEM scan engine is built to capture a vast array of 1D and stacked symbologies, whether displayed on paper, plastic or a digital screen. Stacked linear barcodes that can be read include PDF, MicroPDF, Codablock, GS1 DataBar stacked and composite codes.

Ready for Challenges

Barcode labels encountered in the real world are often in a less than ideal condition, which can make them difficult to scan. Empowered by Cino's FuzzyScan imaging platform, the SE380 is able to read various challenging and problematic barcodes, for example: low contrast, damaged, smudged, or poorly-printed barcodes.

Exceptional Reading Performance

In addition to an exceptional scan range on regular barcodes, the SE380 also delivers superior readings on high-density barcodes. Its performance and capabilities make it a versatile scan engine that is well-suited for diverse applications.

Miniature, Lightweight, Easy-to-Integrate

Ultra-compact and lightweight, the SE380 can be easily integrated into various portable or stationary devices, even those with space constraints, such as hand-held or fixed scanners, mobile computers, or PDAs.

SPECIFICATIONS

Performance Characteristics

| | |
|---------------------|--|
| Optical System | High-performance linear imaging engine |
| Print Contrast | 20% minimum reflective difference |
| Minimum Resolution | Typical 3 mil (Code 39, PCS 0.9) |
| Reading Range *1 | Up to 24 inches on 100% UPC/EAN symbols Up to 34 inches on 20 mil Code 39 |
| Light Source | 630nm visible red LED |
| Scan Rate | Dynamic scanning rate, up to 500 scans per second |
| Reading Direction | Bi-directional (forward and backward) |
| Scan Angle | 42° |
| Pitch/Skew | ± 65° / ± 55° |
| Operating Modes | Low power, Trigger, Force, Level, Alternative, Presentation |
| Host Interfaces | TTL RS-232 serial, USB HID (USB Keyboard), USB COM port emulation |
| Configuration Setup | Command barcodes, API serial command |
| Data Editing | DataWizard Premium |

Physical Characteristics

| | |
|---------------|---|
| Dimensions | 23.0 mm (D) x 21.0 mm (W) x 11.9 mm (H) 0.91 in. (D) x 0.82 in. (W) x 0.47 in. (H) |
| Weight | 6 g |
| Input Voltage | 3.3VDC ± 10% |
| Current | Scanning : Typical 145 mA @3.3VDC Standby : 50 µA @3.3VDC |
| Connector | 12-pin low profile |

1. The Reading Range are measured under Cino's test environmental condition.
2. Don't stare into the LED beam.

Supported Symbolgies

| | |
|-------------------------|--|
| 1D Linear Barcodes | Code 39, Code 39 Full ASCII, Code 32, Code 39 Trioptic, Code 128, GS1-128, Codabar, Code 11, Code 93, Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5, German Postal Code, China Postal Code, IATA, UPC/EAN/JAN, UPC/EAN/JAN with Addendum, Telepen, MSI/Plessey & UK/Plessey, GS1 DataBar (formerly RSS) Linear |
| Stacked Linear Barcodes | GS1 DataBar Stacked, PDF417, Micro PDF417, Codablock F, Composite |

User Environment

| | |
|------------------------|--|
| Operating Temperature | -20 °C to 60 °C (-4 °F to 140 °F) |
| Storage Temperature | -40 °C to 70 °C (-40 °F to 158 °F) |
| Humidity | 5% to 95% related humidity, non-condensing |
| Ambient Light Immunity | 0-100,000 lux |

Safety & Regulatory

| | |
|---------------|---------------------------------------|
| Safety *2 | LED Eye Safety IEC62471, Exempt Group |
| Environmental | Compliant with RoHS directive |

Evaluation Kit



Evaluation Board



Cable Set